



# EUROPEAN PATENT OFFICE

## Patent Abstracts of Japan

PUBLICATION NUMBER : 06100818  
 PUBLICATION DATE : 12-04-94




APPLICATION DATE : 17-09-92  
 APPLICATION NUMBER : 04273846




APPLICANT : SHIN ETSU CHEM CO LTD;


INVENTOR : OKAMI TAKEHIDE;



INT.CL. : C09D 11/10 C08K 3/04 C08L 83/05  
 C08L 83/06 C08L 83/08 C09D 11/00  
 H01B 1/22



TITLE : CONDUCTIVE INK COMPOSITION  
 RESISTANT TO OIL AND FAT AND  
 CONTACT MEMBER



ABSTRACT : PURPOSE: To improve the adhesion to an insulating silicone rubber by compounding two specific organopolysiloxanes, organohydrogenpolysiloxanes, platinum or a platinum compd., a particulate conductive carbon, and a solvent.

CONSTITUTION: This conductive ink compsn. contains an organopolysiloxane which has a viscosity at 25°C of 100cSt or higher and at least two alkenyl groups directly bonded to Si atoms in the molecule and in which at least 30% of all the org. groups except the alkenyl groups are Q<sup>1</sup>-Rf<sup>1</sup> groups [wherein Rf<sup>1</sup> is a 1-20C perfluoroalkyl (ether) group; and Q<sup>1</sup> is a divalent hydrocarbon group], organohydrogenpolysiloxanes comprising organohydrogenpolysiloxanes of formulae I, II, III, and IV and/or an organohydrogenpolysiloxane of formula V and having at least two Si-H bonds in the molecule, platinum or a platinum compd., a particulate conductive carbon, and a polysiloxane having at least one Si-H bond and an alkoxy group and/or an epoxy group in the molecule.

COPYRIGHT: (C)1994,JPO&Japio